

PT4 PRESSURE TRANSMITTER

FEATURES AND SPECIFICATIONS

- ☆ Pressure sensitive piezo-based cell with strong Primary output signal for precise and noise-free operation
- ☆ Pressure cell protected by oil filled pressure enclosure
- ☆ Output signal 4 to 20 mA
- ☆ Separate electrical plug for easy field service
- ☆ Vibration and pulsation resistant
- ☆ Compact dimensions
- ☆ Pressure connector 1/4" SAE female (7/16-20 UNF) with shraeder depressor
- ☆ Variable supply voltage (10-28 VDC)
- ☆ Protection class IP 65, per: EN60529
- ☆ Maximum Working Pressure: 500 psig
- ☆ CE-mark under EC EMC-Directive
- ☆ Lifetime = 5,000,000 full stroke cycles
- ☆ UL file number: E258370
- ☆ CRN file number: OF0845.9 (see page A)



Plug/Cable
assembly sold
seperately

NOMENCLATURE EXAMPLE: PT4-07S

PT4	07S	
	Pressure Range	
Pressure Transmitter	07	22" Hg to 100 psig
	18	0 to 260 psig
	30	0 to 440 psig
	50	0 to 725 psig

ORDERING INFORMATION

PCN	Description
802 320	PT4-07S
802 322	PT4-18S
802 324	PT4-30S
802 326	PT4-50S
804 595	PT4-L60 Plug/Cable Assembly